

# ORIGAMI


---

A unique handcrafted  
wallcovering made from  
wood veneer



INSTYLE


# ORIGAMI




Aspen ORI-13




Natural ORI-03



Cedar ORI-02




Umber ORI-19




Fossil ORI-17



Shadow ORI-18



Verdigris ORI-10



Abalone ORI-16



Royal ORI-21



Pewter ORI-20

Patterns shown are not to scale  
Product may vary in colour due to the nature of the media  
Please refer to website for current colour range





FACE COMPOSITION	paulownia veneer
BACKING TYPE	recycled paper
WIDTH	91cm
WEIGHT	237gsm / 216g lineal m
PATTERN REPEAT	non-match
ROLL SIZE	10.9m approx. Note: minimum order quantity is 10.9m and 3.6m multiples
PERFORMANCE	Untyped Wallcovering
FIRE RATING AS/NZS 3837	BCA Group 1 Av. Specific Extinction Area 132.5m2/kg
Additional Fire Tests	ASTM E-84 Tunnel Test Class A
PLEASE NOTE	ORIGAMI may exhibit variations of colour and texture. This is integral to the beauty and character of the handcrafted organic material. Seams may be obvious upon installation and there will be a panelling effect.

## ENVIRONMENT

- Renewable + recycled content

## PRODUCT INSTALLATION

- Please refer to installation instructions for ORIGAMI supplied with each shipment. A copy is available on our website.
- All material must be installed in numerical sequence as cut from the roll.

## CARE + MAINTENANCE

- Due to the delicate nature of the finishes, care must be taken not to damage or mark the surface due to abrasion / rubbing.
- General maintenance can be achieved with periodic dusting or vacuuming with a soft brush attachment.
- Remove ordinary dirt and smudges with a mild soap and warm water solution.
- Always test the solution on an inconspicuous portion of the wallcovering before proceeding, checking that there is no adverse effect on finish, colour or gloss.
- Care should be taken on dark colours due to the possibility of causing 'light marks'. Always use a blotting action rather than rubbing to avoid abrasion.
- Rinse thoroughly with clean water from the top down using a sponge.
- Dry with a soft lint free cloth or towel.
- Avoid alcohol / solvent based cleaners.
- Please refer to the ORIGAMI care and maintenance instructions for further details. A copy is available on our website.

## WARRANTY

- For a period of 3 years from date of invoice this wallcovering is guaranteed to be first quality and free of manufacturing defects. This warranty applies only to professionally applied installations according to the recommended installation instructions, and proper care and maintenance using appropriate cleaning agents as outlined in the care and maintenance instructions.

