

# WOOD LEAF

---

An elegant timber  
wallcovering with an  
organic leaf pattern

INSTYLE

# WOOD LEAF



White WLE02



Birch WLE06



Natural WLE01



Sage WLE04



Silver WLE05



Charcoal WLE03

Patterns shown are not to scale  
Product may vary in colour due to the nature of the media  
Please refer to website for current colour range





|                            |   |
|----------------------------|---|
| FACE COMPOSITION           | paulownia wood  |
| BACKING TYPE               | recycled paper  |
| WIDTH                      | 91cm  |
| WEIGHT                     | 238gsm / 217g lineal m  |
| PATTERN REPEAT             | non-match   |
| ROLL SIZE                  | 10.9m approx. Note: minimum order quantity is 10.9m and 3.6m multiples  |
| PERFORMANCE                | Untyped Wallcovering  |
| FIRE RATING<br>AS/NZS 3837 | BCA Group 1<br>Av. Specific Extinction Area 132.5m <sup>2</sup> /kg   |
| Additional Fire Tests      | ASTM E-84 Tunnel Test Class A   |
| NOTE                       | WOOD LEAF may exhibit variations of colour and texture. This is integral to the beauty and character of the handcrafted organic material.<br>Seams may be obvious upon installation and there will be a panelling effect. |

#### ENVIRONMENT

- Rapidly-renewable + recycled content

#### PRODUCT INSTALLATION

- Please refer to installation instructions for WOOD LEAF supplied with each shipment and available from our website.
- All material must be installed in numerical sequence as cut from the roll.

#### CARE + MAINTENANCE

- Due to the delicate nature of the finishes, care must be taken not to damage or mark the surface due to abrasion / rubbing.
- General maintenance can be achieved with periodic dusting or vacuuming with a soft brush attachment.
- Remove ordinary dirt and smudges with a mild soap and warm water solution.
- Always test the solution on an inconspicuous portion of the wallcovering before proceeding, checking that there is no adverse effect on finish, colour or gloss.
- Care should be taken on dark colours due to the possibility of causing 'light marks'. Always use a blotting action rather than rubbing to avoid abrasion.
- Rinse thoroughly with clean water from the top down using a sponge.
- Dry with a soft lint free cloth or towel.
- Avoid alcohol / solvent based cleaners.
- For further details please refer to the WOOD LEAF care and maintenance instructions available from our website.

#### WARRANTY

- For a period of 3 years from date of invoice this wallcovering is guaranteed to be first quality and free of manufacturing defects. This warranty applies only to professionally applied installations according to the recommended installation instructions, and proper care and maintenance using appropriate cleaning agents as outlined in the care and maintenance instructions.

