




COMPOSITION	100% olefin								
WIDTH	188cm								
WEIGHT	256gsm								
PATTERN REPEAT	H 18cm V 15.4cm								
ROLL SIZE	50m approx.								
CARE CODE	Screens								
CTA RATING	 COMMERCIAL SCREEN FABRICS								
LIGHTFASTNESS AS 2001.4.21	>6								
FIRE RATINGS AS/NZS 1530.3	<table border="0"> <tr> <td>Ignitability</td> <td>0</td> </tr> <tr> <td>Spread of Flame</td> <td>0</td> </tr> <tr> <td>Heat Evolved</td> <td>0</td> </tr> <tr> <td>Smoke Developed</td> <td>3</td> </tr> </table>	Ignitability	0	Spread of Flame	0	Heat Evolved	0	Smoke Developed	3
Ignitability	0								
Spread of Flame	0								
Heat Evolved	0								
Smoke Developed	3								
AS/NZS 3837	BCA Group 2 Av. Specific Extinction Area 273.7 m2/kg								
APPLICATION	screens, panels								

ENVIRONMENT

- 100% low embodied-energy material: olefin has a lower embodied-energy compared to polyester and nylon.
- Environmentally Improved Production Process: reduced energy consumption, reuse and recycling of waste

GREEN STAR

- SEEK can be used on white furniture certified to Ecospecifier, AFRDI, ECNZ and GECA.
- The Green Star Rating Tool states “Where at least 90% of an item’s mass is certified to a GBCA recognised standard, the item can be entered as a certified product at Level A, B or C.” Therefore any fabric can be used as fabrics are almost always under 10% by weight of a furniture item.