

INSTALLATION INSTRUCTIONS

WALLCOVERINGS: JAKARTA

Important Notice About Materials

- Do not attempt to cut or install this material until you have read the instructions below in full.
- All rolls must have the same production dye lot number. Hang in sequence as cut from roll.
- Avoid folding or creasing that may create markings on this product.
- Vinyl wallcoverings in certain environments have a tendency to panel. Seaming and shading due to lighting and other environmental attributes are considered normal.
- **JAKARTA is meant to mimic a natural product. Due to this a panel effect is expected and is not a defect. Please check material for defects prior to installation. Product claims will not be considered on cut or installed material after three panels have been hung.**
- Consult with your designer or Instyle if you have any questions regarding seams and the paneling effect of this product.

Prior to Installation

- Examine each roll to be sure the product is what was ordered. Each roll should be rolled out so colour and shading can be examined to your satisfaction.
- If working around switch plates, please turn off electricity.

Wall Preparation

1. Strip wall of any existing wallcoverings, and remove any loose / flaking paint and old adhesive. Fill any cracks with packing compound and sand any bumps for mirror smooth finish to prevent imperfections from telegraphing through material.
2. Clean wall and remove any dirt, grease, or soap. Materials will not adhere if not properly cleaned.
3. Monitor wall moisture levels. A wall that is not properly prepared or that has too much moisture content may not be conducive to proper adhesion.
4. Always apply a single coat of pigmented sealer on new and unpainted walls, followed by an acrylic or latex primer / sizer that is made specifically for wallcoverings.

Important Notes for Application

- We recommend a mould inhibiting, pre-mixed, heavy-duty clay based adhesive be used. Do not dilute the adhesive.
- Apply paste with roller to ensure even application taking care not to get adhesive on surface. Do not use a pasting machine and avoid excessive soaking of material.
- Booking varies with backing and climate. Take into consideration the humidity and temperature of your workspace when hanging all materials. Booking times generally vary between 8-15 minutes depending on the material and installation climate. It is recommended the installation location is climate controlled.
- Paste and hang one strip at a time. Hang materials in sequence as cut from the roll.
- Carefully inspect the installation after applying three strips before proceeding. If, at any time during the installation, a discrepancy occurs, stop. Contact the designer or Instyle before proceeding.

Hanging and Trimming of Materials

- JAKARTA is untrimmed and is intended to be [↑]table[↓] trimmed and butted on the wall using a fresh blade and straight edge for each cut.
- JAKARTA is recommended to be reverse hung. [↑]_↓
- Product may be trimmed on the wall using an overlap and double cut method. Do not score wall when overlapping and double cutting, as this will result in seam separation.
- All seams should be taped using only low adhesive tape (safe release tape), such as 3M Blue tape. This is to keep the seam surface clean when overlapping and/or butting materials.
- As each strip is installed, remove excess adhesive from the surface. Always use a clean sponge and clean water to wipe seams.
- To remove air pockets, sweep face of goods using a standard vinyl sweep (25mm bristles).
- Vinyl can be wrapped around a corner. Materials will soften once adhesive is applied to back. When installing around corners, material must wrap by at least 15cm

CARE AND MAINTENANCE INSTRUCTIONS

VINYL WALLCOVERINGS: JAKARTA

Cleaning

- General maintenance can be achieved with periodic dusting or vacuuming of wallcovering. We recommend when vacuuming that you only use a soft brush attachment to avoid damaging the material. We recommend you avoid using dusting sprays such as Pledge, as these chemicals may alter the colour of the product.

Marks and Stains

- When cleaning marks and stains, we recommend you test on a sample or inconspicuous portion of the wallcovering before proceeding to be sure that there will not be an adverse effect on colour or gloss.
- Remove ordinary dirt and smudges with a mild soap and warm water solution. Avoid all solvent based cleaners.
- Only use soft or natural sponges, an abrasive sponge can damage wallcovering.
- Avoid soaking wallcovering as this may damage material. It is recommended you ring out your sponge prior to cleaning.
- More care should be taken in cleaning dark colours due to the possibility of causing 'light marks'.
- Always use a blotting action rather than a rubbing or scrubbing motion to avoid abrasion.
- Very lightly rinse material with clean water and sponge after cleaning.
- Dry immediately with soft, lint-free cloth or towel.

Stubborn Marks and Stains (ink, tar, gum, blood, crayon, glue, etc)

All stains should be attempted to be removed as above with soap and water first. Isopropyl alcohol (rubbing alcohol) may set some stains that soap and water may remove. If stain or mark persists we recommend you spray with a solution of isopropyl alcohol (rubbing alcohol). Then wipe away in a circular motion using soap and water with a sponge

For glue stains during installation, Coca-Cola or Sprite are the recommended cleaning solution. Black coffee can also remove dried glue stains.