

# Ecoustic® SC Panel

—  
An acoustic panel with a solid colour (SC) profile ideal for exposed edge applications



INSTYLE

# Colours

## Solid Colour 9mm



Milk



Dune



Marble



Dapple



Zinc



Alloy



Equinox



Zodiac

## Solid Colour 12mm



Snowdrop



Almond



Horizon



Fawn



Truffle



Arizona



Venus




Oxide



Cool



Atom



Cirrus



Tungsten



Galaxy



Cave



Leaf



Olive



Isle



Azure



Bluebell



Denim



Iris

## Solid Colour 24mm



Pure



Stone



Ash



Graphite



Nero

Custom colours are available, minimums apply

Product may vary in colour due to the nature of the media  
Please refer to website for current colour range

# Ecoustic® Solid Colour Panel



PRODUCT	Ecoustic® Solid Colour Panel (SC)		
COMPOSITION	100% PET		
THICKNESS	9mm, 12mm (+/-1mm approx.) 24mm (+/-2mm approx.)		
WEIGHT	9mm: 1900gsm / 12mm: 2400gsm		
DIMENSIONS	9mm: 1220 x 2440mm approx. 12mm: 1220 x 2800mm approx. 24mm: 1210 x 2720mm approx.		
LIGHTFASTNESS ISO 105-B02	>7		
FIRE RATINGS	9mm	12mm	24mm
AS/NZS 1530.3	9	8	8
Ignitability	9	8	8
Spread of Flame	0	0	0
Heat Evolved	3	1	1
Smoke Developed	6	5	5
AS/ISO 9705	BCA Group 1 SMOGR <100  NZBC Group 1-S		
ASTM E84	9mm: Class C 12mm: Class A		
ACOUSTIC	Refer to acoustic info on following page		
APPLICATION	Workstation screen, partition, wall panel, ceiling		
PLEASE NOTE	Onsite trimming to square each panel is essential. Variation in thickness, fibre mix, colour as well as flecks + surface blemishes are an inherent + unavoidable feature. Variations from panel to panel can occur, panel joins may be obvious upon installation creating a panelling effect. Installation may require onsite adjustment by the contractor to achieve a professional finish + minimal variation. Results from performance tests are guidelines only		

## BENEFITS

**Lightweight, Easy to Handle + Install:** Compared to traditional panels, Ecoustic® SC is lower in weight, easier to handle and results in reduced transportation costs. Ecoustic® SC can be trimmed and installed without the need for additional finishes, which reduces labour and material costs. Installation + Care Guidelines are available on our website

**Edging Profile:** 9mm, 14.5mm + 25mm natural anodised aluminium edging length + T Trims in natural anodised or black powdercoat at 2750mm (+/- 5mm) are available

## Designed for the Environment



**Building Rating Systems:** SC panels will contribute the following points for Green Star, LEED + WELL building standards.

Criteria	Green Star	LEED	WELL
Low VOC	√	√	√
Stewardship - Recycling	√	√	NA
Cradle to Cradle Bronze Certification	-	√	√
Declare Label	NA	√	√
Manufacturer EMS	√	NA	NA
Toxic Material Reduction	NA	NA	√

## HOW TO SPECIFY


PRODUCT	Ecoustic® Solid Colour Panel
THICKNESS	9mm, 12mm or 24mm
COLOUR	Select from applicable SC colours for nominated thickness

# Acoustic Performance

The sound absorption has been tested in accordance with AS/ISO 354

9mm NRC 0.3 /  $\alpha_w$  0.2 (Direct Fix)  
 12mm NRC 0.4 /  $\alpha_w$  0.25 (Direct Fix)  
 24mm NRC 0.65 /  $\alpha_w$  0.45 (Direct Fix)

For complete test reports please contact your local distributor




Frequency	$\alpha_s$ 9mm	$\alpha_s$ 12mm	$\alpha_s$ 24mm
100	0.03	0.07	0.06
125	0.00	0.01	0.07
160	0.01	0.02	0.10
200	0.02	0.02	0.14
250	0.04	0.04	0.19
315	0.06	0.08	0.31
400	0.09	0.12	0.46
500	0.12	0.19	0.57
630	0.20	0.28	0.70
800	0.29	0.39	0.83
1000	0.38	0.53	0.92
1250	0.49	0.65	0.93
1600	0.59	0.75	0.99
2000	0.68	0.82	0.98
2500	0.74	0.85	0.98
3150	0.77	0.90	0.98
4000	0.82	0.91	0.94
5000	0.81	0.82	0.91
NRC	0.3	0.4	0.65

Ecoustic® SC 24mm is ideal for medium to high frequency absorption.

The sound absorption has been tested in accordance with AS/ISO 354

9mm NRC 0.85 /  $\alpha_w$  0.78 (200mm air gap)  
 12mm NRC 0.85 /  $\alpha_w$  0.8 (200mm air gap)  
 24mm NRC 0.95 /  $\alpha_w$  0.95 (200mm air gap)

For complete test reports please contact your local distributor



Frequency	$\alpha_s$ 9mm	$\alpha_s$ 12mm	$\alpha_s$ 24mm
100	0.47	0.62	0.39
125	0.56	0.69	0.38
160	0.69	0.71	0.55
200	0.75	0.91	0.76
250	0.96	0.92	0.80
315	0.92	0.87	0.94
400	1.00	1.08	1.02
500	1.06	0.96	1.05
630	0.87	0.84	1.04
800	0.73	0.74	0.95
1000	0.71	0.76	0.86
1250	0.78	0.88	0.99
1600	0.81	0.84	1.00
2000	0.76	0.79	0.94
2500	0.77	0.76	0.90
3150	0.80	0.79	0.89
4000	0.78	0.74	0.88
5000	0.79	0.76	0.85
NRC	0.85	0.85	0.95