

SPLICE

—
A high performance
wallcovering inspired by
deconstructed exposed
elements



INSTYLE

SPLICE



Argent SPL-001



Alloy SPL-002



Bole SPL-004



Forest SPL-003

Patterns shown are not to scale
Product may vary in colour due to the nature of the media
Please refer to website for current colour range



FACE COMPOSITION	vinyl (PVC), metal film
BACKING TYPE	nonwoven
WIDTH	137cm (untrimmed)
WEIGHT	452gsm / 620g lineal m
PATTERN REPEAT	H 127cm V 91.5cm
ROLL SIZE	7.3m approx. Note: All colourways sold by the full 7.3m roll
PERFORMANCE	Type II Wallcovering Ideal for high traffic environments
FIRE RATING AS/NZS 3837	BCA Group 2 Av. Specific Extinction Area 653.4 m2/kg
Additional Fire Tests	ASTM E-84 Tunnel Test Class A
NOTE	Wallcovering colouration may vary from batch to batch. Product will not be supplied that does not meet Innovations production standards.

ENVIRONMENT

- Low VOC
- Phthalate free

PRODUCT INSTALLATION

- Please refer to installation instructions for SPLICE supplied with each shipment. A copy is also available on our website, or obtained by contacting your nearest office or agent.
- All material must be installed in numerical sequence as cut from the roll.

CARE + MAINTENANCE

- General maintenance can be achieved with periodic dusting or vacuuming with a soft brush attachment.
- Remove ordinary dirt and smudges with a mild soap and warm water solution. Always test the solution on an inconspicuous portion of the wallcovering before proceeding, checking that there is no adverse effect on finish, colour or gloss. Care should be taken on dark colours due to the possibility of causing 'light marks'. Always use a blotting action rather than rubbing to avoid abrasion. Rinse thoroughly with clean water from the top down using a sponge.
- Deeply embossed wallcoverings need extra attention in case suds or loosened dirt lodge in depressed surfaces.
- Dry wallcovering with a soft lint free cloth or towel.
- Please refer to the SPLICE care and maintenance instructions for further details. A copy is available on our website or obtained by contacting your nearest office or agent.

WARRANTY

- For a period of 3 years from date of invoice this wallcovering is guaranteed to be first quality and free of manufacturing defects. This warranty applies only to professionally applied installations according to the recommended installation instructions, and proper care and maintenance using appropriate cleaning agents as outlined in the care and maintenance instructions.