

DESIGN	Ecoustic® Baffle Banner Ecoustic® Baffle Incline Ecoustic® Baffle Ebb Ecoustic® Baffle Apex
PROFILE THICKNESS	Solid Colour SC 24mm or 12mm Felt Screen 25mm or 12mm
COLOUR	Solid Colour SC 24mm (5 colours) Felt Screen 25mm (34 colours - white or black core depending on felt colour) Solid Colour SC 12mm (15 colours) Felt Screen 12mm (34 colours - white or black core depending on felt colour)
DIMENSIONS	up to 2700mm lengths 100 - 1200mm depths
SUSPENSION SYSTEM	<p>Natural or black anodised aluminium extrusions are supplied with each baffle in standard 2700mm lengths</p> <p>Ecoustic® Baffle is available with or without our six suspension hardware system options</p> <p>HARDWARE OPTIONS</p> <p>Ecoustic® Vertical Cable Suspension Ecoustic® Vertical Cable Installation - Screw Fix Set or Ecoustic® Vertical Cable Installation - Mount Plate Set Optional: Suspended ceiling grid clip</p> <p>Ecoustic® Suspended 'Tee' Bar Ecoustic® T-Bar Installation Set NB: Tee bar to be supplied by others to suit site requirements Please nominate 15, 24 or 32mm T-Bar size</p> <p>Ecoustic® Slung Cable Suspension Ecoustic® Slung Cable Installation Set NB: Cable not included due to varying site requirements</p> <p>Ecoustic® Metal Rod Suspension Ecoustic® Rod Installation Set NB: Metal rod not included due to varying site requirements</p> <p>Ecoustic® Collar Strap Ceiling Collar Strap Installation Set 3m rolls can be supplied by Instyle or purchased externally Cut to length on site by installers, the collar strap is used to secure baffle extrusions to structural supports of unique site specific dimensions</p> <p>Ecoustic® Unistrut Installation Set</p> <p>Direct Fix Ecoustic® Baffle Extrusion Direct Fix On Site Mechanical fasteners to suit site structure</p>