

Oasis



Lotus OAS-01



Citta 0AS-02



Freya OAS-03



Kali OAS-06



Weldon OAS-04



Maitri OAS-05



Rivona OAS-07

Specialty Wallcoverings



FACE COMPOSITION

Polyester, linen, cellulose

BACKING TYPE

Non-woven

WIDTH

135cm

WEIGHT

289gsm / 389g lineal m

PATTERN REPEAT

Non-match

ROLL SIZE

27m approx. NB: minimum order quantity is 10.9m and 0.9m multiples

Untyped Wallcovering

PERFORMANCE FIRE RATING

ASTM E-84 Tunnel Test Class A

PRODUCT INSTALLATION

- Please refer to installation instructions for Oasis supplied with each shipment. A copy is also available on our website.
- All material must be installed in numerical sequence as cut from the roll.

CARE + MAINTENANCE

- Due to the delicate nature of the finishes, care must be taken not to damage or mark the surface due to abrasion / rubbing.
- General maintenance can be achieved with periodic dusting or vacuuming with a soft brush attachment.
- Remove ordinary dirt and smudges with a mild soap and warm water solution.
- Always test the solution on an inconspicuous portion of the wallcovering before proceeding, checking that there is no adverse effect on finish, colour or gloss.
- Care should be taken on dark colours due to the possibility of causing 'light marks'. Always use a blotting action rather than rubbing to avoid abrasion.
- Dry with a soft lint free cloth or towel.
- Avoid alcohol / solvent based cleaners.
- Oasis care and maintenance instructions are available on our website.

WARRANTY

For a period of 3 years from date of invoice this wallcovering
is guaranteed to be first quality and free of manufacturing
defects. This warranty applies only to professionally applied
installations according to the recommended installation
instructions, and proper care and maintenance using
appropriate cleaning agents as outlined in the care and
maintenance instructions.







