

ANVERS

A linen-look high performance wallcovering with a subtle natural pleated texture

INSTYLE

Anvers



Abrams AVR-001



Bennett AVR-002



Bonds AVR-003



Caldwell AVR-004



Hicks AVR-006



James AVR-007



May AVR-008



Powers AVR-009



Scott AVR-010



Snyder AVR-011



Taylor AVR-012



Upton AVR-015



Hampton AVR-005



Wood AVR-014



Warner AVR-013

Patterns shown are not to scale
Product may vary in colour due to the nature of the media
Please refer to website for current colour range

INSTYLE



FACE COMPOSITION	vinyl
BACKING TYPE	osnaburg
WIDTH	137cm
WEIGHT	452gsm / 619g lineal m
PATTERN REPEAT	non-match
ROLL SIZE	27.4m approx. Note: minimum order quantity is 10.9m and 0.9m multiples
PERFORMANCE	Type II Wallcovering
FIRE RATING AS/NZS 3837 AS 5637.1	BCA Group 2 Av. Specific Extinction Area 51.3 m2/kg
ISO 5660.1	NZBC Group 2S Av. Specific Extinction Area 5.2 m2/kg
Additional Fire Tests	ASTM E-84 Tunnel Test Class A

PRODUCT INSTALLATION

- Refer to our detailed installation instructions for Anvers supplied with each shipment before cutting or installing this wallcovering. A copy can also be downloaded from our website. Hang material in sequence as cut from the roll.

CARE + MAINTENANCE

- General maintenance can be achieved with periodic dusting or vacuuming with a soft brush attachment.
- Remove ordinary dirt and smudges with a mild soap and warm water solution.
- Avoid all solvent based cleaners.
- Always test the solution on an inconspicuous portion of the wallcovering before proceeding, checking that there is no adverse effect on finish, colour or gloss.
- Care should be taken on dark colours due to the possibility of causing 'light marks'. Always use a blotting action rather than rubbing to avoid abrasion.
- Dry with a soft lint free cloth or towel.
- Anvers care and maintenance instructions are available on our website.

WARRANTY

- For a period of 3 years from date of invoice this wallcovering is guaranteed to be first quality and free of manufacturing defects. This warranty applies only to professionally applied installations according to the recommended installation instructions, and proper care and maintenance using appropriate cleaning agents as outlined in the care and maintenance instructions.

