

CALIBRE

—

A stunning highly-durable
wool-rich texture with
coloured highlights

INSTYLE


CALIBRE



CALIBRE Worth



CALIBRE Class




CALIBRE Distinction



CALIBRE Squire




CALIBRE Forte




CALIBRE Quality




CALIBRE Character



CALIBRE Paramount



CALIBRE Talent



CALIBRE Courage



CALIBRE Aria



CALIBRE Luminary




CALIBRE Ultimate



CALIBRE Aesthetic




CALIBRE Grade




CALIBRE Virtue



CALIBRE Literary



CALIBRE Keynote



CALIBRE Icon



CALIBRE Status



CALIBRE Opus



CALIBRE Merit



CALIBRE Fine




CALIBRE Business



CALIBRE Honours

Product may vary in colour due to the nature of the media
Patterns shown are not to scale
Please refer to website for current colour range


CALIBRE



CALIBRE Noble



CALIBRE Dandy




CALIBRE Integrity




CALIBRE Title



CALIBRE Elite



CALIBRE Principle



CALIBRE Esteem

Product may vary in colour due to the nature of the media
Patterns shown are not to scale
Please refer to website for current colour range



COMPOSITION	82% Australian and New Zealand wool, 18% nylon	
WIDTH / WEIGHT	137cm / 456gsm	
PATTERN REPEAT	nil	
ROLL SIZE	52m approx.	
CARE CODE	CTA 1	
ABRASION		
Martindale AS2001.2.25	>100,000	
Wyzenbeek ASTM 4157	27,000 double rubs	
CTA RATING	<div style="display: flex; align-items: center;"> <div style="background-color: #333; color: white; padding: 5px; font-weight: bold; font-size: 1.2em; margin-right: 5px;">hc</div> <div> <p>HEAVY DUTY COMMERCIAL USE</p> </div> </div>	
SEAM SLIPPAGE	Warp 5.4mm Weft 4.1mm	
AS2001.2.22	Note: All seams must be overlocked or secured to prevent the premature failure of the seam due to fraying	
PILLING	4	
Martindale IWS196		
LIGHTFASTNESS	>5	
ISO 105-B02		
FIRE RATINGS	Ignitability	0
AS/NZS 1530.3	Spread of Flame	0
	Heat Evolved	0
	Smoke Developed	4
AS/NZS 3837	BCA Group 2	
	Av. Specific Extinction Area 45.5 m ² /kg	
ISO 5660.1	NZBC Group 2-S	
	Av. Specific Extinction Area 40.3m ² /kg	
IMO Resolution A.625(16)	Sections 8.2 + 8.3: Pass	
Additional Fire Tests	California 117E, ASTM E84	
APPLICATION	upholstery, screens, wall panels	
ORIGIN	Made locally	
PLEASE NOTE	Results from performance tests are guidelines only Interior products must be protected from direct heat and sunlight	

ENVIRONMENT

- 82% sustainable, rapidly renewable Australian + NZ wool
- Manufactured to strict environmental criteria, reduced water (6% savings) and energy use, non-potable water supply (100% rain and ground water), recycling of waste
- Manufacturer has a certified EMS (Enviro-Mark Diamond)
- CALIBRE is certified low VOC
- Wool absorbs indoor air contaminants, benefiting indoor air quality
- 82% biodegradable (natural fibre content) + recyclable

GREEN STAR

CALIBRE can contribute points to the following Green Star criteria:

- Stewardship Programs: CALIBRE can be reused or recycled through our Revive recycling program
- Low-VOC
- CALIBRE can be used on white furniture certified to Ecospecifier, AFRDI, ECNZ and GECA
- The Green Star Rating Tool states “Where at least 90% of an item’s mass is certified to a GBCA recognised standard, the item can be entered as a certified product at Level A, B or C.” Therefore any fabric can be used as fabrics are almost always under 10% by weight of a furniture item

LEED

CALIBRE can contribute points to the following LEED criteria:

- Bio-Based + Rapidly-Renewable Content (82%)
- Low-VOC
- Extended Producer Responsibility Recycling Program

WELL

CALIBRE can contribute to the following WELL criteria:

- Low VOC / VOC Reduction: CALIBRE is low VOC
- Toxic Material Reduction: CALIBRE is free of PFCs, flame retardants, phthalates and urea formaldehyde