



COMPOSITION 100% polyester

WIDTH / WEIGHT 148cm / 660gsm

PATTERN REPEAT H 2cm V 1.8cm

ROLL SIZE 25m approx.

CARE CODE CTA 1

ABRASION

Martindale AS2001.2.25 25,000

Wyzenbeek ASTM D4157-13 50,000 double rubs

SEAM SLIPPAGE Warp 1.2mm Weft 1.3mm

AS2001.2.22 Note: All seams must be overlocked or

secured to prevent the premature failure of the seam due to fraying A light or medium ballpoint needle is

recommended

PILLING 3/4

Martindale IWS196

LIGHTFASTNESS >5

ISO 105 B02

FIRE RATINGS Ignitability 11
AS/NZS 1530.3 Spread of Flame 0

Heat Evolved 4
Smoke Developed 5

AS/NZS 3837 (AS 5637.1) BCA Group 1

Av. Specific Extinction Area 40.2 m²/kg

ISO 5660.1 NZBC Group 3

Av. Specific Extinction Area 39.8m²/kg

Cal 117E Pass

APPLICATION upholstery, screen, wall panel

PLEASE NOTE Results from performance tests are

guidelines only

IMPORTANT

- It is recommended that foam is placed between solid edges of furniture and surface upholstery to support the fabric against damage
- A light or medium ballpoint needle is recommended

