



# Ecooustic® Ceiling Flats


—  
Highly functional, decorative ceiling tiles  
for new and existing grid systems



**Front View**  
600 Tile: 595 x 595mm



**Side View**



**Front View**  
1200 Tile: 1195 x 595mm



PRODUCT	Ecoustic® Ceiling Flats
DESCRIPTION	Highly functional, decorative ceiling tiles designed to fit into new and existing grid systems, available in various sound-absorbing thicknesses
COMPOSITION	100% PET (13.5mm, 25mm: <60% recycled PET)
DIMENSIONS	600 Tile: 595mm (w) x 595mm (h) 1200 Tile: 1195mm (w) x 595mm (h) Drops into new or existing T-Frame suspended ceiling systems with a nominal 600 x 600mm or 1200 x 600mm grid
THICKNESS	Available in four thicknesses: 12mm, 13.5mm, 24mm and 25mm
ACOUSTIC	SC 12mm: NRC 0.85 (200mm airgap) Felt 13.5mm: NRC 0.85 (400mm airgap) SC 24mm: NRC 0.95 (200mm airgap) Felt 25mm: NRC 0.9 (400mm airgap) Refer to acoustic graph on next page
FIRE TEST AS/ISO 9705	Group 1 SMOGRA <100
APPLICATION	Drop-in ceiling tiles
WARRANTY	A 12 month warranty is provided against manufacturing defects. This applies to internal installation only, outdoor use will void any warranty

HOW TO SPECIFY	
PRODUCT	Ecoustic® Ceiling Flats
TILE SIZE	600 Tile or 1200 Tile
THICKNESS	12mm, 13.5mm, 24mm or 25mm
COLOUR	Select from relevant colours for nominated thickness: Ecoustic® Felt or SC

## Designed for the Environment

- Ecoustic® Ceiling Flats 13.5mm + 25mm: <60% recycled content, EPD + Greentag Level A certified
- SC is ISO 14001-certified EMS + Cradle to Cradle Bronze certified




**Building Rating Systems:** Ceiling Flats will contribute the following points for Green Star, LEED + WELL building standards.


Criteria	Green Star	LEED	WELL
<b>Recycled Content</b> Felt 13.5mm + 25mm	✓	✓	NA
<b>Low VOC</b>	✓	✓	✓
<b>Stewardship - Recycling</b>	✓	✓	NA
<b>Manufacturer Certified EMS</b> SC Panel	✓	NA	NA
<b>EPD</b> Felt 13.5mm + 25mm	✓	✓	NA
<b>Declare Label</b>	NA	✓	✓
<b>Greentag Level A Certification</b> Felt 13.5mm + 25mm	✓	✓	✓
<b>C2C Certification</b> SC Panel	-	✓	✓
<b>Toxic Material Reduction</b>	NA	NA	✓
<b>Sound Reducing Surfaces</b>	NA	NA	✓

Please contact your representative for CAD drawings

Ecoustic® Ceiling Flats 12mm	NRC 0.85 / $\alpha_w$ 0.8 (200mm airgap)
Ecoustic® Ceiling Flats 13.5mm	NRC 0.85 / $\alpha_w$ 0.85 (400mm airgap)
Ecoustic® Ceiling Flats 24mm	NRC 0.95 / $\alpha_w$ 0.95 (200mm airgap)
Ecoustic® Ceiling Flats 25mm	NRC 0.90 / $\alpha_w$ 0.90 (400mm airgap)








Ecoustic® Ceiling Flats (per box in a single colour)  
 12 + 13.5mm: 16 x 600 Tiles / 8 x 1200 Tiles  
 24 + 25mm: 8 x 600 Tiles / 4 x 1200 Tiles

Drop Ceiling Frame  
 15mm + 24mm Exposed Tee grid system  
 [ Not supplied ]

## Ecoustic® SC 12mm



## Ecoustic® SC 24mm



## Ecoustic® Panel 13.5mm + 25mm



## IMPORTANT

**Drop Ceiling Specification:** Ecoustic® Ceiling Flats are designed to be compatible with 15mm and 24mm Exposed Tee grid systems. Ensure the tile is suitable for your selected system prior to ordering.

**Moisture Absorption:** After four days at 50°C, 95% RH the moisture absorbency of SC 12mm and SC 24mm was less than 0.3% and 2.9% by weight respectively. Ecoustic® Felt 13.5mm + 25mm: Exposure to an atmosphere of 50% and 95% RH for four days provides moisture absorption of less than 0.2% per volume. As Ecoustic® Ceiling Flats is 100% polyester, it will not degrade over time due to moisture, mildew or rot in office environments.

**Fixtures:** Any fixtures must be supported independent to the Ecoustic® Ceiling Flats tile. The tiles can be cut on site to accommodate for new and existing lighting and fixtures. When cutting use a new blade for each cut and ensure the area to be cut is fully supported throughout. Cut from the tile face with care.

**HVAC:** Ensure Ecoustic® Ceiling Flats are compliant with the specified HVAC system. Ecoustic® Ceiling Flats are recommended for Ducted Return Air and is not Plenum Return Air rated.

**Back Loading:** Ecoustic® Ceiling Flats are not suitable for back loading. Loads must be supported independently by the grid or through the use of additional fixtures.

**Toxicity:** Polyester is non-toxic and is classed the same as wood under the State of New York Article 15 Part 1120. Ecoustic® Ceiling Flats do not contain any Red List Chemicals (USA EPA).