JAKARTA

A high performance wallcovering with a linen-look texture



JAKARTA

High Performance Wallcoverings



Oatmeal JKT20



Shell JKT13




Spearmint JKT27



Dovetail JKT21



Quartz JKT12



Oasis JKT26



Bronze JKT09



Storm JKT22



Greyscale JKT23



Horseshoe JKT24



Pond JKT25

Please refer to physical sample as colour may vary from screen



JAKARTA

High Performance Wallcoverings



FACE COMPOSITION	vinyl (PVC)
BACKING TYPE	non-woven
WIDTH	137cm
WEIGHT	453gsm / 667g lineal m
PATTERN REPEAT	non-match
ROLL SIZE	27.4m approx. Note: minimum order quantity is 10.9m and 0.9m multiples
PERFORMANCE	Type II Wallcovering
FIRE RATING AS/NZS 3837 AS 5637.1	BCA Group 2 Av. Specific Extinction Area 51.3 m2/kg
ISO 5660.1	NZBC Group 2S Av. Specific Extinction Area 5.2 m2/kg
Additional Fire Tests	ASTM E-84 Tunnel Test Class A

PRODUCT INSTALLATION

- Please refer to installation instructions for JAKARTA supplied with each shipment and available on our website.
- All material must be installed in numerical sequence as cut from the roll.

CARE + MAINTENANCE

- General maintenance can be achieved with periodic dusting or vacuuming with a soft brush attachment.
- Remove ordinary dirt and smudges with a mild soap and warm water solution. Always test the solution on an inconspicuous portion of the wallcovering before proceeding, checking that there is no adverse effect on finish, colour or gloss. Care should be taken on dark colours due to the possibility of causing 'light marks'. Always use a blotting action rather than rubbing to avoid abrasion. Rinse thoroughly with clean water from the top down using a sponge.
- Deeply embossed wallcoverings need extra attention in case suds or loosened dirt lodge in depressed surfaces.
- Dry wallcovering with a soft lint free cloth or towel.
- Please refer to the JAKARTA care and maintenance instructions for further details.

WARRANTY

 For a period of 3 years from date of invoice this wallcovering is guaranteed to be first quality and free of manufacturing defects. This warranty applies only to professionally applied installations according to the recommended hanging instructions, and proper care and maintenance using appropriate cleaning agents as outlined in the care and maintenance instructions.



